



# OmniAire 1200PAC

Omnitec Design, Manufacturing Air Purification Equipment Since 1988

The **OmniAire Portable Air Cleaner (PAC)** machine with 99.99% HEPA and UVGI germicidal lights eliminates sub-micron particulates and microbial contamination. Designed for healthcare environments, it offers quiet operation as the air is exhausted through the HEPA filter. This unit has fully adjustable air flow and a small footprint.

## OmniAire 1200 PAC is used for:

- Air Purification and Sterilization in Healthcare
- Veterinary Clinics
- Hospital Pharmacies - USP 797 Requirements
- First Response Shelters, Mobile Hospitals
- Laboratories, Clean Rooms
- Isolation Rooms - Positive or Negative Room Pressurization
- Morgues & Mortuaries
- Archives



## OmniAire 1200 PAC Specifications:

- Air flow:** 200 to 1100 cfm with variable speed control
- Filtration:** Primary Filter - 40% Pleated Filter  
HEPA Filter - 99.99%, .3μ, metal frame, 16"x16"x12", individually tested and Certified
- Power:** 115 Volts, 60 Hz, 6 amp maximum
- Controls:** Recessed panel with Variable Speed Control  
Differential pressure indicator, 0-3" WC to indicate HEPA filter loading;  
Hour meter with LCD display;  
UVGI lights ON/OFF switch and lamps/ballast status LED lights;
- Construction:** Aluminum Housing with Galvanized Metal reinforcements paint, riveted and silicone sealed
- Size:** 19" x 22" x 42" high with 3" casters
- Weight:** 105 lbs.
- Connections:** Inlet with 16"x16" pleated filter and protective screen. Discharge on top through HEPA and protective screen

ORDERING INFO .....	PART #
OmniAire 1200PAC .....	OA1200PAC
HEPA Filter 99.99%, 0.3μ .....	OAH1616G
Primary Pleated Filter .....	OFP16
Connection Adapter, 10" .....	OAIM10
Quick Clamp, 10" .....	QC10
Flexible Duct, 10"x25' .....	OAD10
OdorGuard 600 Carbon Filter .....	OG1616
OdorGuard 750 Plus Carbon Filter .....	OGP1616
UV-C Emitter Tube, 10½" J .....	EUV105JD

## Optional accessories:

- Connection adapter for 10" diameter flex hose on the discharge and/or suction side
- OdorGuard 600 high capacity carbon fiber filter
- OdorGuard 750 high capacity carbon/alumina fiber filter

## Note:

- OmniAire 1200 PAC can be ordered to operate on 230 VAC/60-50 Hz
- Also available in a 99.99% @ .1-.2μ HEPA Filter



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

3067108

[www.omnitecdesign.com](http://www.omnitecdesign.com)

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983